DH-MV-SI5600MG000E



- Powerful intel platform, easy for secondary development
- Support standard 2.5mm audio interface
- 8G memory and 128G SSD internal storage
- Software trigger/Hardware trigger/Free run mode
- Industrial grade M12 connector
- 1Gbps Ethernet industrial interface, max 100m transmission

Specification


Model	Sensor	Sensor type	Shutter	Resolution	Frame rate (fps)	Bit depth	Interface	Mono/Color	Pixel size (μm)	Sensor size
DH-MV-SI5600MG000E	IMX178	CMOS	Rolling	3072x2048	30	12	GigE	Mono	2.4x2.4	1/1.8"

Model	DH-MV-SI5600MG000E
Effective Pixels	6.3MP
Operating System	Win 10 X64 OS
Processor	Intel Apollo Lake platform
SNR	>38dB
Dynamic Range	66dB
Interface	3 physical interface: 1 GigE, 1 GPIO, 1 USB & VGA port
GPIO	12 pins IO interface: 3 input without opto isolation, 3 output without opto isolation
Image Format	Mono8/10/12
Gain	X1~X6
Gamma	Range from 0 to 4, support LUT
Memory	DDR4 8G Byte
Storage	External storage: support maximum 32GB SD card; Internal storage: maximum 128GB SSD
Exposure Time	208.6μS~1S
Trigger Mode	Software trigger/Hardware trigger/Free run mode
User Setting	Support two sets of user-defined configurations
Dimensions	132.2mm x 69mm x 62mm
Weight	<2kg
LED indicator	5 status indicators: 1 system, 2 network and 2 user configurable indicators
Lens Mount	Support C / M12 mount
Power Supply	Support 24V DC power supply
Power Consumption	≤30W
Temperature	Storage temperature:-30° C~ + 80° C; Operation temperature: 0° C~+50° C

Rev 001.001 2018 Dahua. All rights reserved. Design and specifications are subject to change without notice.


Spectrogram


SI5600MG000E




Quantum Efficiency Curve for Mono Sensor

Dimensions





IO Interface Instruction



Pin	Signal	Description
1	OPT_IN1	Opto-isolated input 1
2	OPT_IN2	Opto-isolated input 2
3	OPT_OUT1	Opto-isolated output 1
4	OPT_OUT2	Opto-isolated output 2
5	RXD RS232	Serial port input
6	OPT_IN_GND	Opto-isolated in ground
7	Power	DC 24V input
8	GND	Power ground
9	OPT_OUT_GND	Opto-isolated out ground
10	OPT_IN0	Opto-isolated input 0
11	OPT_OUT0	Opto-isolated output 0
12	TXD RS232	Serial port output